

Cummins (DCEC) Generator Parameters

Model	Standby Power		Prime Power		Engine	Alternator	Dimension	Weight
	kVA	kW	kVA	kW	Model	Stamford Model	mm	KG
DCEC CUMMINS SERIES (50hz, 1500RPM, 3 Phase, 400 V / 230 V - N)								
KH-16GF	22	18	20	16	4B3.9-G1	PI144D	1660x750x1200	800
KH-16GF	22	18	20	16	4B3.9-G2	PI144D	1660x750x1200	800
KH-20GF	28	22	25	20	4B3.9-G1	PI144E	1660x750x1200	800
KH-20GF	28	22	25	20	4B3.9-G2	PI144E	1660x750x1200	800
KH-24GF	33	26	30	24	4BT3.9-G1	PI144G	1660x750x1200	800
KH-24GF	33	26	30	24	4BT3.9-G2	PI144G	1660x750x1200	800
KH-32GF	44	35	40	32	4BT3.9-G1	PI144J	1660x750x1200	810
KH-32GF	44	35	40	32	4BT3.9-G2	PI144J	1660x750x1200	810
KH-44GF	61	48	55	44	4BTA3.9-G2	UCI224C	1860x750x1200	850
KH-60GF	83	66	75	60	4BTA3.9-G11	UCI224E	1900x800x1250	950
KH-80GF	110	88	100	80	6BT5.9-G1	UCI224G	2160x800x1300	1100
KH-80GF	110	88	100	80	6BT5.9-G2	UCI224G	2160x800x1300	1100
KH-96GF	132	106	120	96	6BTA5.9-G2	UCI274D	2160x800x1300	1100
KH-108GF	149	119	135	108	6BTAA5.9-G2	UCI274E	2300x850x1300	1400
KH-120GF	165	132	150	120	6BTAA5.9-G12	UCI274F	2300x850x1300	1400
KH-144GF	198	158	180	144	6CTA8.3-G1	UCI274G	2400x860x1380	1440
KH-144GF	198	158	180	144	6CTA8.3-G2	UCI274G	2400x860x1380	1440
KH-160GF	220	176	200	160	6CTAA8.3-G2	UCI274H	2500x960x1450	1700
KH-200GF	275	220	250	200	6LTAA8.9-G2	HCI444C	2640x970x1450	2000
KH-360GF	495	396	450	360	QSZ13-G2	HCI544C	3150x1360x1870	2600
KH-400GF	550	440	500	400	QSZ13-G3	HCI544C	3150x1360x1870	2670