

Import Cummins (Produced in USA) Generator Parameters

Model	Standby Power		Prime Power		Engine	Alternator	Dimension	Weight
	kVA	kW	kVA	kW	Model	Stamford Model	mm	KG
IMPORTED CUMMINS SERIES (50hz, 1500RPM, 3 Phase, 400 V / 230 V - N)								
KH-250GF	344	275	313	250	QSL9-G5	HCI444E	3150x1100x1920	2420
KH-380GF	523	418	475	380	QSL15-G6	HCI544C	3430x1200x2065	4100
KH-400GF	550	440	500	400	QSL15-G8	HCI544C	3430x1200x2065	4250
KH-500GF	688	550	625	500	VTA28-G5	HCI544F	4067x1880x2286	5450
KH-600GF	825	660	750	600	VTA28-G6	HCI634G	4067x1880x2286	5900
KH-640GF	880	704	800	640	QSK23-G3	HCI634G	4593x1562x2086	6200
KH-720GF	990	792	900	720	QST30-G3	HCI634H	4757x1702x2332	6500
KH-800GF	1100	880	1000	800	QST30-G4	HCI634J	4757x1800x2332	6700
KH-1500GF	2063	1650	1875	1500	QSK60-G3	PI734E	6175x2600x2840	15152
KH-1600GF	2200	1760	2000	1600	QSK60-G4	PI734F	6175x2600x2840	15366
KH-1800GF	2475	1980	2250	1800	QSK60-G13	PI734G	6175x2600x2840	17217
KH-2000GF	2750	2200	2500	2000	QSK78-G9	LVSI804R	7158x2800x2900	24880
KH-2400GF	3300	2640	3000	2400	QSK78-G6	LVSI804T	7158x2800x2900	25280