

Perkins Generator Parameters

Model	Standby Power		Prime Power		Engine	Alternator	Dimension	Weight
	kVA	kW	kVA	kW	Model	Model	mm	KG
PERKINS SERIES (50hz, 1500RPM, 3 Phase, 400 V / 230 V - N)								
KH-7GF	10	8	9	7	403A-11G1	PI044E	1100x450x940	290
KH-7GF	10	8	9	7	403D-11G	PI044E	1100x450x940	290
KH-10GF	14	11	13	10	403A-15G1	PI044F	1200x500x1000	380
KH-10GF	14	11	13	10	403D-15G	PI044F	1200x500x1000	380
KH-12GF	17	13	15	12	403A-15G2	PI044G	1300x500x1000	415
KH-16GF	22	18	20	16	404A-22G1	PI144D	1350x530x1000	456
KH-16GF	22	18	20	16	404D-22G	PI144D	1350x530x1000	456
KH-24GF	33	26	30	24	1103A-33G	PI144G	1740x730x1565	762
KH-36GF	50	40	45	36	1103A-33TG1	UCI224D	2030x730x1565	870
KH-48GF	66	53	60	48	1103A-33TG2	UCI224E	2030x730x1565	870
KH-52GF	72	57	65	52	1104A-44TG1	UCI224F	2135x730x1595	980
KH-64GF	88	70	80	64	1104A-44TG2	UCI224G	2135x730x1595	1020
KH-64GF	88	70	80	64	1104C-44TAG1	UCI224G	2135x730x1595	1020
KH-80GF	110	88	100	80	1104C-44TAG2	UCI274C	2235x730x1595	1090
KH-108GF	149	119	135	108	1106A-70TG1	UCI274E	2565x730x1575	1376
KH-120GF	165	132	150	120	1106A-70TAG2	UCI274F	2565x730x1575	1420
KH-144GF	198	158	180	144	1106A-70TAG3	UCI274G	2645x730x1630	1644
KH-160GF	220	176	200	160	1106A-70TAG4	UCI274H	2645x730x1630	1695
KH-180GF	248	198	225	180	1506A-E88TAG2	UCDI274J	3035x900x1525	1695
KH-200GF	275	220	250	200	1506A-E88TAG3	HCI444C	3035x900x1525	2035
KH-220GF	303	242	275	220	1506A-E88TAG4	HCI444D	3100x900x1600	2600
KH-240GF	330	264	300	240	1506A-E88TAG5	HCI444D	3200x900x1700	3000
KH-280GF	385	308	350	280	2206C-E13TAG2	HCI444E	3500x1105x1960	3385
KH-320GF	440	352	400	320	2206C-E13TAG3	HCI444F	3500x1105x1960	3385
KH-360GF	495	396	450	360	2506C-E15TAG1	HCI544C	3935x1150x2080	3583
KH-400GF	550	440	500	400	2506C-E15TAG2	HCI544D	3935x1150x2080	3691
KH-480GF	660	528	600	480	2806C-E18TAG1A	HCI544E	3960x1535x2100	4298
KH-520GF	715	572	650	520	2806A-E18TAG2	HCI544F	3960x1535x2100	4453
KH-600GF	825	660	750	600	4006-23TAG2A	HCI634G	4450x1650x2290	5413
KH-640GF	880	704	800	640	4006-23TAG3A	HCI634G	4450x1710x2290	5422
KH-720GF	990	792	900	720	4008TAG1A	HCI634H	4700x2045x2475	7600
KH-800GF	1100	880	1000	800	4008TAG2A	HCI634J	4700x2045x2475	7639
KH-1000GF	1375	1100	1250	1000	4012-46TWG2A	PI734A	5220x2130x2600	9230
KH-1080GF	1485	1188	1350	1080	4012-46TWG3A	PI734B	5220x2130x2600	9400
KH-1200GF	1650	1320	1500	1200	4012-46TAG2A	PI734C	5220x2130x2600	9550
KH-1320GF	1815	1452	1650	1320	4012-46TAG3A	PI734D	5220x2130x2600	9720
KH-1480GF	2035	1628	1850	1480	4016TAG1A	PI734E	5220x2130x2600	10000
KH-1480GF	2035	1628	1850	1480	4016-61TRG1	PI734E	5220x2130x2600	13155
KH-1600GF	2200	1760	2000	1600	4016TAG2A	PI734F	5770x2800x3520	13450
KH-1600GF	2200	1760	2000	1600	4016-61TRG2	PI734F	5770x2800x3520	13450
KH-1800GF	2475	1980	2250	1800	4016-61TRG3	PI734G	5770x2800x3520	13450